

Electric powered forklift 2.0 t

Truck specifications				8FBE20T
Identification	1.1	Manufacturer		Toyota
	1.2	Model		8FBE20T
	1.3	Drive		Electric
	1.4	Operator type		Rider seated
	1.5	Load capacity/rated load	Q	kg 2000
	1.6	Load centre	c	mm 500
	1.8	Load distance, centre of drive axle to fork	x	mm 317
	1.9	Wheelbase	y	mm 1521
	2.1	Service weight		3342
Weight	2.2	Axle load, with load, front/rear		4746/596
	2.3	Axle load, without load, front/rear		1619/1723
	3.1	Tyre - pneumatic (P), pneumatic shaped cushion (SE), solid rubber (R)		SE
Tyres	3.2	Tyre size, front		200/50-10
	3.3	Tyre size, rear		140/55-9
	3.5	Wheels, number front/rear (x = driven wheels)		2x2
	3.6	Track width, front	b ₁₀	mm 925
	3.7	Track width, rear	b ₁₁	mm 186,2
	4.1	Tilt of mast/fork carriage forward/backward	α/β	deg 5/7
	4.2	Height, mast lowered	h ₁	mm 2120
Dimensions	4.3	Free lift	h ₂	mm 115
	4.4	Lift	h ₃	mm 3300
		Lift height	h ₂₃	mm 3335
	4.5	Height, mast extended	h ₄	mm 3870
	4.7	Height of overhead guard (cab)	h ₆	mm 2055
	4.8	Seat height/stand height	h ₇	mm 1059
	4.12	Coupling height	h ₁₀	mm 543
	4.19	Overall length	l ₁	mm 2988
	4.20	Length to face of forks	l ₂	mm 1988
	4.21	Overall width	b ₁	mm 1152
	4.22	Fork dimensions	s/e/l	mm 35/120/1000
	4.23	Fork carriage DIN 15 173, class/type A, B		IIA
	4.24	Fork-carriage width	b ₃	mm 920
	4.31	Ground clearance, with load, below mast	m ₁	mm 90
	4.32	Ground clearance, centre of wheelbase	m ₂	mm 97
Performance data	4.33	Aisle width for pallets 1000x1200 crossways	A _{st}	mm 3318
	4.34	Aisle width for pallets 800x1200 lengthways	A _{st}	mm 3440
	4.35	Turning radius	W _a	mm 1671
	4.36	Internal turning radius	b ₁₃	mm 0
	5.1	Travel speed, with/without load		km/h 16/16
	5.2	Lift speed, with/without load		m/s 0,38/0,54
	5.3	Lowering speed, with/without load		m/s 0,52/0,50
	5.5	Drawbar pull, with/without load	N	4839/5046
	5.6	Max. drawbar pull, with/without load	N	9145/9188
Electric motor	5.7	Gradeability, with/without load	%	13,2/24,4
	5.8	Max. gradeability, with/without load	%	18,0/24,4
	5.9	Acceleration time, with/without load	s	4,7/4,3
	5.10	Service brake		Hydraulic
	6.1	Drive motor rating S2 60 min	kW	6x2
	6.2	Lift motor rating S3 15%	kW	11,7
	6.3	Battery acc. to DIN 43 531/35/36 A, B, C, no		43 531A
	6.4	Battery voltage, nominal capacity K _s	V/Ah	48/660
Other	6.5	Battery weight	kg	1013
	6.6	Energy consumption acc. to EN16796:2016	kWh/h	4,5
	8.1	Type of drive control		inverter MOSFET
	8.2	Operating pressure for attachments	bar	183
	8.3	Oil volume for attachments	l/min	41,3
	8.4	Sound level at the driver's ear according to EN 12 053	dB(A)	69,7

All data are based on table configuration. Other configurations may give other values.

Truck performance and dimensions are nominal and subject to tolerances.

Products and specifications are subject to change without notice.

Mast dimensions and rated capacities

Model			V					FV					FW					FSV					FSW										
8FBE20T	Lift height	h_{23}	3035	3335	3535	3735	4035	4535	5035	3035	3335	3535	3735	3035	3335	3535	3735	4335	4535	5035	5535	6035	4335	4535	4735	5035	5535	6035	6535	7035	7535		
	Lift	h_3	3000	3300	3500	3700	4000	4500	5000	3000	3300	3500	3700	3000	3300	3500	3700	4300	4500	4700	5000	5500	6000	4300	4500	4700	5000	5500	6000	6500	7000	7500	
	Height, mast lowered	h_1	1970	2120	2220	2380	2570	2820	3070	1970	2120	2220	2380	2000	2150	2250	2350	1970	2040	2120	2220	2380	2570	1980	2050	2150	2250	2450	2600	2800	3000	3200	
	Height, mast extended ¹⁾	h_4	3570	3870	4070	4270	4570	5070	5570	3580	3880	4080	4280	3555	3855	4055	4255	4845	5045	5245	5545	6045	6545	4845	5045	5245	5545	6045	6545	7045	7545	8045	
	Height, mast extended ²⁾	h_4	4220	4520	4720	4920	5220	5270	6220	4220	4520	4720	4920	4220	4520	4720	4920	5520	5720	5920	6220	6720	7220	5520	5720	5920	6220	6720	7220	7720	8220	8720	
	Free lift, without load backrest	h_2	80	80	80	80	80	80	80	80	1430	1580	1680	1840	1440	1590	1690	1790	1460	1530	1610	1710	1870	2060	1430	1500	1600	1700	1900	2050	2250	2450	2650
	Free lift, with load backrest	h_2	80	80	80	80	80	80	80	80	750	900	1000	1160	780	930	1030	1130	750	820	900	1000	1160	1350	760	830	930	1030	1230	1380	1580	1780	1980

1) Without load backrest

2) With load backrest; Height of standard load backrest is 1220 mm.

Pneumatic shaped cushion tyre			V					FV					FW					FSV					FSW									
8FBE20T	Tilt range, forward	deg	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5				
	Tilt range, backward	deg	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	7(5)	5				
	Load capacity at 500 mm LC	kg	2000	2000	2000	2000	2000	2000	1950	2000	2000	2000	2000	2000	2000	2000	2000	1950	1920	1900	1800	1650	1550	1950	1920	1900	1850	1750	1550	1250	1000	800

Data in () are for when "Cabin Series" is selected (minimum front windshield).

